



# SURROUND BE

## Product Data Sheet

Surround Be features an exclusive "Bi/Twin" design with twin inputs, enabling the loudspeaker to be used both in 5.1 (Bipolar mode) or 7.1 (double mono mode). Why? To avoid having multiple surround loudspeakers in your Home Cinema.



### Key points

- Compact high-performance loudspeaker
- Speaker drivers developed and manufactured in France by Focal

### Standard finish



Black Lacquer



5.1 set-up



7.1 set-up

Type	Two-way sealed bipolar surround loudspeaker
Drivers	2 x 6 1/2" (16.5 cm) "W" cone bass/midrange 2 x 1 1/16" (27 mm) pure Beryllium inverted dome tweeters
Frequency response (+/- 3dB)	72Hz - 40kHz
Low frequency point - 6dB	59Hz
Sensitivity (2.83V / 1m)	91dB
Nom. impedance	4 Ohms / 8 Ohms
Minimum impedance	3 Ohms / 6 Ohms (bipolar/mono)
Crossover frequency	2400Hz
Recommended amplifier power	40 - 200W
Dimensions (HxLxP)	15 <sup>23/64</sup> x16 <sup>59/64</sup> x7 <sup>31/64</sup> " (390x430x190mm)
Net weight	27.77lbs (12.6kg)